

VEGA LOUNGE SERIES

PRODUCT: VEGA LOUNGE SERIES

CODES: VE-01, VE-02, VE03, VE04



SINGLE SOLID SEAT DOUBLE SOLID SETTEE SINGLE OPEN SEAT DOUBLE OPEN SETTEE

CODE: VE-01| VE-02| VE-03| VE-04|

DIMENSIONS. (METRIC mm)

<u>Overall Depth.</u>	630	630	600	600
<u>Overall Width.</u>	710	1310	680	1270
<u>Overall Height.</u>	800	800	780	780
<u>Seat Height.</u>	490	490	450	450
<u>Seat Depth.</u>	490	490	500	500

=====

DIMENSIONS. (IMPERIAL INCHES)

<u>Overall Depth.</u>	24.8"	24.8"	23.6"	23.6"
<u>Overall Width.</u>	28"	51.6"	26.7"	50"
<u>Overall Height.</u>	31.5"	31.5"	30.7"	30.7"
<u>Seat Height.</u>	19.2"	19.2"	17.7"	17.7"
<u>Seat Depth.</u>	19.2"	19.2"	19.6"	19.6"

VEGA – LOUNGE - SPECIFICATIONS

OPEN FRONT

FRAME CONSTRUCTION

FSC® Certified Plywood. Furniture grade fibreboard.

FOAM

Combustion Modified High Resilience (CMHR) foam

FEET

Black polypropylene glides

CLOSED FRONT

FRAME CONSTRUCTION

FSC® Certified Plywood. Furniture grade fibreboard.

FOAM

Combustion Modified High Resilience (CMHR) foam

FEET

Black polypropylene glides



FABRIC – JUST COLOR - CHIEFTAIN



Blupuffin Designs
Suite 207, 264 Midpark Avenue SE | Calgary , Alberta, Canada
www.blupuffin.com | sales@blupuffin.com

FABRIC – JUST COLOR - CHIEFTAIN

Composition:	Surface: PVC Backing: Cotton/PES
Total weight:	705g/m ²
Thickness:	1.10mm
Bursting strength:	1,200+ kPa
Abrasion:	100,000+ Martindale rubs
Roll length:	25m
Width:	137-139cm
Flame retardancy:	BS5852 Ignition Source 5 – Crib 5 BS7176 Medium Hazard S.I.1988 No. 1324 Schedule 4 and 5 BS EN1021-1 and 2 CS-25 FMVSS 302 IMO A 652 (16)
Antimicrobial:	Independent testing has verified that Just Colour fabric is effective at reducing the spread of MRSA, E.Coli and other similar bacteria. JIS Z 2801:2000
Cleaning instructions:	Clean regularly with a damp soapy cloth and rinse well with clean water to retain appearance and durability. Difficult substances including ink, lipstick and food colouring must be removed immediately to avoid staining. A soft brush can be used for heavy or ingrained soiling. For infection control, the fabric can be cleaned with a solution of disinfectant specified by manufacturers. When using bleach, a 5% (50,000 PPM) solution is acceptable.